


ZF0350W



CHIMNEY FLANGE DIMS:

O.D. = 17" I.D. = 12-1/4" B.C.D = 14-1/2" NO. OF HOLES = 8 HOLE DIAMETER = 0.53"





SIDE VIEW

		ή	_
^			
			*
L — I	-	L -	l I_
	REAF	RVIEW	

FRONT VIEW

	BOILER MODEL - ZF350W	INCHES	METRIC
Α	LENGTH OF BASE	78	1981
A1	LENGTH OF SUPPORT FROM BASE		-
В	HEIGHT	80 1/2	2044
C	WIDTH OF BASE	43 1/2	1105
D	CTR. LOWER DRUM TO CTR. UPPER DRUM	61 1/2	1562
Ε	CENTER OF LOWER DRUM TO BOTTOM	9 1/2	241
F	CENTER OF BURNER OPENING TO BOTTOM	31	787
G	INLET / OUTLET FLANGE. CLASS 150	4	102
Н	NOZZLE CLEARANCE FROM TOP, FRONT	14 1/4	362
J	CENTER OF FLUE GAS OUTLET TO REAR	16	406
K	DRUM CLEARANCE FROM BASE, FRONT	1 3/4	44
L	TUBE REMOVAL CLEARANCE FROM BASE	26	660
М	UPPER DRUM, OD, NPS	8 5/8	219
N	LOWER DRUM, OD, NPS	8 5/8	219
0	FLUE GAS OUTLET, ID	12	305
Р	NOZZLE CLEARANCE FROM BASE, REAR	20 1/8	511
Q	BLOWDOWN, NPT	1 1/2	38
R	BURNER DIMENSION	39 1/2	1003
W	OVERALL BOILER LENGTH	112 3/8	2854
Х	OVERALL BOILER LENGTH WITH BURNER	137 5/8	3496

NOTE: DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE CONSULT FACTORY FOR CERTIFIED DIMENSIONS.

| UNILUX ADVANCED MFG., LLC 30 COMMERCE PARK DRIVE NO COMMERCE PARK

NOTE: "X" DIMENSION MAY VARY BASED ON BURNER